

Did You Know Your Toolholders Don't Fit Your CNC Mills?

J&M Machine ran the tests and found that standard retention knobs cause the toolholder shank to expand at the small end.



TAPER SHANK TEST FIXTURE*

*Patent Pending

Once you install the standard retention knobs into your toolholders, we're willing to bet that they are outside the AT3 spec.

That's why we developed the TAPER SHANK TEST FIXTURE.*

When toolholders are distorted, the large end is free to move from side to side in the spindle while cutting.

The affects of this movement are:

- ✗ Toolholder run-out
- ✗ Vibration
- ✗ Breakage of tool razor edges

Why is this important?

- ✓ Proper seating of holders in the spindles
- ✓ Reduces toolholder movement while cutting
- ✓ Increases tool life & feed rates
- ✓ Allows for maintenance of closer tolerances
- ✓ Eliminates run-out and vibration
- ✓ Ensures better finishes
- ✓ Better balance = less tool life variance
- ✓ Reduces tool breakage
- ✓ Helps guarantee retention knobs are not over-torqued during installation
- ✓ Reduces down-time for machine and spindle maintenance
- ✓ **Reduces milling costs**



Order by phone or write us at sales@jmmachineinc.com

For a distributor near you, drop us an email at sales@jmmachineinc.com.

Visit us online at <http://www.jmmachineinc.com>.
Distributors welcome!



MANUFACTURED BY



1234 High Street | Fairport Harbor, Ohio 44077
USA 800-322-7750 | CANADA 440-357-1234
www.jmmachineinc.com